Power



GUIDANCE CONTROLLER

Paired with any GFX series display, the NAV-500™ guidance controller is an affordable precision solution capable of receiving corrections from multiple GNSS satellite

constellations. Get sub-meter repeatable accuracy and full-farm coverage at a great price to use during tillage, broad-acre seeding, spraying and harvest.

Housing & Mechanical		
Housing Material	Low-profile, chemical-resistant polymer casing	
Size	180 mm x 180 mm x 74 mm	
Weight	640 g	

Universal Magnetic Mounts Mount Power

9-16 VDC, 3.5 W

Connections	
To GFX Series Displays	M12 4-pin connector
For I/O	Deutsch 12-pin connector

Operational Range		
Operating Temperature	-30 °C - +70 °C	
Storage Temperature	-40 °C - +85 °C	
Humidity	100% Condensing	
Ingress Protection	IP66	

Communication and I/O		
Bluetooth	Bluetooth 4.1	
Serial Ports	1TX/RX, 1TX only	
CAN Ports	2	
BroadR-Reach Port	1	
Digital Out	Sonalert	
Analog In	Remote Engage	
NIMEA Output	1, 5, 10, Hz	

Inertial Measurement Unit (IMU)

Gyroscope	3-axis, 50 Hz
Accelerometer	3-axis, 50 Hz
External IMU Needed for EZ-Pilot Pro	57407-01

GNSS Receiver Specifications

Constellations	GPS: L1 C/A
	GLONASS:
	L1 C/A, L1P
	Galileo: E1
	Beidou: B1
	QZSS: L1 C/A
Satellite Corrections	ViewPoint RTX™
	SBAS (WAAS, EGNOS, GAGAN, MSAS)
	SBAS +

Guidance

	EZ Pilot,
Electric	EZ-Pilot Pro,
	EZ-Steer

+++++++++++

- Low-profile rugged housing
- Trimble ViewPoint RTX[™] corrections
- 5 satellite constellations
- Roll-corrected manual guidance
- Compatible with EZ-Steer® assisted steering system and EZ-Pilot® Pro steering system
- 4.1 Bluetooth®

+ + + +

Multiple CAN ports





Vantage New Zealand Level 1, 167 Main Street Methven, NZ 0800 482 682 info@vantage-nz.com www.vantage-nz.com

NORTH AMERICA

Trimble Inc.

10368 Westmoor Drive Westminster, CO 80021

- +1-720-887-6100 Phone
- +1-720-887-6101 Fax

Corporate Headquarters 935 Stewart Drive Sunnyvale, CA 94085

- +1-408-481-8000 Phone
- +1-408-481-7740 Fax

Trimble Germany GmbH Am Prime Parc 11 65479 Raunheim **GERMANY**

- +49-6142-2100-0 Phone
- +49-6142-2100-140 Fax



